



YOUR DRILLING EXPERT

HAJCO
Rock Tools

EXPLORATION & GRADE CONTROL

At Halco Rock Tools we pride ourselves on exemplary levels of customer service, support and training to reflect your drilling needs.

Having manufactured drilling consumables for over sixty five years our support team are well placed to provide accurate and timely solutions to optimise your drilling performance.

Halco Rock Tools is a world class manufacturer of Down-The-Hole (DTH) drilling equipment with locations around the globe, and headquartered in the UK. Halco pioneered the development and distribution of DTH hammers in the 1950s.

Produced for more than 65 years, our products continue to be regarded as one of the most reliable and durable available today. This is due to our commitment to exceeding customer needs, design expertise and rigorous product testing in extreme drilling conditions.

The hammers and drill bits in this catalogue are designed to offer optimum drilling performance in Exploration and Pit Grade Control applications. Additional hammers and bits are available for the following applications:

- Mining and Quarrying
- Oil and Gas
- Exploration

We can offer training in hammer and bit selection, service, maintenance and repair. With specialists available at all of our locations, you're never far away from the support you require. Halco's superb team of engineers are only a phone call away.

Further Learning Aids:

- A-Z of DTH Drilling
- DTH Maintenance Manual
- User Guide
- www.halcorocktools.com

INTRODUCING THE NEW RC400 & RC500

Developed for the Exploration market, our 4" and 5" models include a unique bit retention system for reduced downtime in the event of bit shanking. With an integrated hammer and bit design for improved chip removal and extended bit life, plus increased production rates on our previous models, Exploration drillers can now expect to reach greater depths with improved sample cuttings for longer.

KEY FEATURES AND BENEFITS

- Simple design, easy maintenance and improved reliability
- Integrated hammer and bit design for better chip removal and bit life
- Improved safety features
- Unique bit retention system as standard
- Rapidly reaches full operating pressure
- New check valve design
- 2 piece easy loading sample tube
- Solid piston construction reducing stress and improving life



4"

RC 400

AT A GLANCE




SIZE
127 - 189mm
(5 - 7 1/2")



SHANK
Halco
RC400



AIR PRESSURE
300 - 600 psi
(20 - 41 bar)



Top loading filter to prevent debris entering the hammer

NRV to prevent hammer from flooding

Easy sample tube removal

Piston + liner configuration for optimal air flow

8 spline bit shank gives large drive area and reduces contact stresses

Bit retaining shroud to prevent loss of bit head if failure occurs and seals the hole for sample recovery

RC 400

The Halco RC400 has been designed to give maximum performance in Exploration and Grade control applications. The integral adaptor housing allows easy access to the long lasting sample tubes. The enhanced performance stems from a simple robust design that reduces complicated maintenance procedures, providing less down time and greater savings.

The RC400 also features improved flushing characteristics from high velocity air flow directed through the drill bit. A variety of thread connections are available which includes options for both Remet and Metzke. The RC400 is equipped with an integral Drill Bit Catcher system for added peace of mind. It also has a sub adaptor body to suit most dual wall drill pipes.


The design features of the new RC400 combine to give an increase in drilling ROP, an increase in service life, and most importantly, greater sample recovery quality.

Drill bit diameters of 127 - 136 mm (5" - 5 3/8").

Collaring bit diameter of 189mm (7 1/2").


Suitable for operation at air pressures of 300-600 psi.

Note: Warranty may be void if stated operating parameters are not adhered to.



Figures are based on theoretical data

Available Shanks	Available Bits	Collaring Bit
Halco RC400	127mm (5") 130mm (5 1/8") 133mm (5 1/4") 136mm (5 3/8")	189mm (7 1/2")



Hammer Overview

Hammer Type	RC400		
Part Number	600405	600407	600415
Shank	Halco	Halco	Halco
	RC400	RC400	RC400
Top Thread	Remet 4"	Metzke 4"	Metzke 4.5"
Weight	77 kg	77 kg	77 kg
Outside Diameter	121 mm (4.764")	121 mm (4.764")	121 mm (4.764")
Make Up Length	1306 mm (51.417")	1306 mm (51.417")	1306 mm (51.417")

Parts List

Hammer Type	RC400			
Shank	Remet 4"	Metzke 4"	Metzke 4.5"	
Model Number	600405	600407	600415	
Item	Description	Part Number	Part Number	Part Number
1	Circlip	777048	777048	777048
2	'O' Ring	747120	N/A	N/A
3	Tube Connector	604798	604804	604814
4	Air Filter	604476	604476	604476
5	Top Adaptor	604598	604608	604812
6	'O' Ring	768045	768045	768045
7	NRV Cone	604479	604479	604479
8	NRV Seal	748106	748106	748106
9	NRV Spring	760155	760155	760155
10	Compression Spacer	604800	604800	604800
11	Compression Ring	604799	604799	604799
12	'O' Ring	768217	768217	768217
13	'O' Ring	747120	747120	747120
14	Upper Sample Tube	604599	604599	604599
15	'O' Ring	768213	768213	768213
16	Sample Tube Seal	768148	768148	768148
17	Liner	604596	604596	604596
18	Lower Sample Tube	604597	604597	604597
19	Piston	604595	604595	604595
20	Cylinder	604594	604594	604594
21	Square Snap Ring	604801	604801	604801
22	'O' Ring	768212	768212	768212
23	Guide Bush	604657	604657	604657
24	Round Snap Ring	783061	783061	783061
25	'O' Ring	768043	768043	768043
26	Bit Retaining Rings	604656	604656	604656
27	Shroud	SEE BELOW	SEE BELOW	SEE BELOW
28	Chuck	604655	604655	604655
SK	Service Kit	SK73	SK73	SK73
RK	Repair Kit	RK124	RK124	RK124

Drill Bits

Part Number	Diameter	Face	Buttons	Weight		
Number	Mm	Inch	Design	Type	Qty/dia	(kg)
Halco RC400 - Extra Flushing Design						
653469	127	5	Drop Centre	Domed	12 x 16 mm / 2 x 13 mm	14.1
653470	130	5 1/8	Drop Centre	Domed	12 x 16 mm / 2 x 13 mm	14.1
653471	133	5 1/4	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	14.3
653472	136	5 3/8	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	14.3
653486	189	7 1/2	Drop Centre	Domed	16 x 16 mm / 10 x 13 mm	36.5
Halco RC400 - Heavy Duty Design						
653558	127	5	Drop Centre	Domed	14 x 16 mm / 2 x 13 mm	14.2
653559	130	5 1/8	Drop Centre	Domed	14 x 16 mm / 2 x 13 mm	14.2
653560	133	5 1/4	Drop Centre	Domed	14 x 16 mm / 4 x 13 mm	14.4
653561	136	5 3/8	Drop Centre	Domed	14 x 16 mm / 4 x 13 mm	14.4

Shroud

Outside Diameter	Part Number
125 mm	604602
128 mm	604603
131 mm	604604
134 mm	604605
187 mm	601423

Your Drilling Expert



AT A GLANCE



SIZE
137 - 189mm
(5 3/8 - 7 1/2")



SHANK
Halco
RC500



AIR PRESSURE
300 - 600 psi
(20 - 41 bar)

Top loading filter to prevent debris entering the hammer

NRV to prevent hammer from flooding

Easy sample tube removal

Piston + Liner configuration for optimal air flow

8 spline bit shank gives large drive area and reduces contact stresses

Bit Catcher to prevent loss of bit head if failure occurs and seals the hole for sample recovery

RC 500

The Halco RC500 has been designed to give maximum performance in Exploration and Grade control applications. The integral adaptor housing allows easy access to the long lasting sample tubes. The enhanced performance stems from a simple robust design that reduces complicated maintenance procedures, providing less down time and greater savings.

The RC500 also features improved flushing characteristics from high velocity air flow directed through the drill bit. A variety of thread connections are available which includes options for both Remet and Metzke. The RC500 is equipped with an integral Drill Bit Catcher system for added peace of mind. It also has a sub adaptor body to suit most dual wall drill pipes.


The design features of the new RC500 combine to give an increase in drilling ROP, an increase in service life, and most importantly, greater sample recovery quality.

Drill bit diameters of 137 - 146 mm (5 3/8" - 7 1/2").

Collaring bit diameter of 189mm (7 1/2").

Suitable for operation at air pressures of 300-600 psi.

Air Consumption (CFM)




Figures are based on theoretical data

Available Shanks
Halco RC500

Available Bits
137mm (5 3/8")
140mm (5 1/2")
143mm (5 5/8")
146mm (5 3/4")

Collaring Bit
189mm (7 1/2")



Hammer Overview

Hammer Type	RC500	
Part Number	600409	600410
Shank	Halco	Halco
	RC500	RC500
Top Thread	Remet 4.5"	Metzke 4.5"
Weight	89 kg	89 kg
Outside Diameter	132 mm (5.196")	132 mm (5.196")
Make Up Length	1388 mm (54.645")	1388 mm (54.645")

Parts List

Hammer Type	RC500				
Shank	Remet 4.5"	Metzke 4.5"	SK	RK	CK
Model Number	600409	600410	Contents		
Item	Description	Part Number	Part Number	Quantities	
1	Circlip	777049	777049	-	1
2	'O' Ring	768215	N/A	3	-
3	Tube Connector	604807	604808	-	1
4	Air Filter	604622	604622	-	-
5	Top Adaptor	604616	604617	-	-
6	'O' Ring	768196	768196	1	1
7	NRV Cone	604545	604545	-	-
8	NRV Seal	748104	748104	1	1
9	NRV Spring	760157	760157	-	1
10	Compression Spacer	604811	604811	-	-
11	Compression Ring	604810	604810	1	1
12	'O' Ring	768218	768218	2	2
13	'O' Ring	768215	768215	1	1
14	Upper Sample Tube	604618	604618	-	1
15	'O' Ring	768214	768214	2	2
16	Sample Tube Seal	768210	768210	1	5
17	Liner	604614	604614	-	-
18	Lower Sample Tube	604615	604615	-	5
19	Piston	604665	604665	-	-
20	Cylinder	604611	604611	-	-
21	Square Snap Ring	604313	604313	-	1
22	'O' Ring	768055	768055	1	1
23	Guide Bush	604660	604660	-	-
24	Round Snap Ring	783062	783062	1	1
25	'O' Ring	768091	768091	1	1
26	Bit Retaining Rings	604659	604659	-	1
27	Shroud	SEE BELOW	SEE BELOW	-	-
28	Chuck	604658	604658	-	1
SK	Service Kit	SK75	SK75	-	-
RK	Repair Kit	RK126	RK126	-	-
CK	Consumer Kit	CK04	CK05	-	-

Drill Bits

Part Number	Diameter		Face Design	Buttons Type	Buttons Qty/dia	Weight (kg)
	Mm	Inch				
Halco RC500						
653554	137	5 3/8	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	27.4
653555	140	5 1/2	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	27.6
653556	143	5 5/8	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	27.8
653557	146	5 3/4	Drop Centre	Domed	12 x 16 mm / 4 x 13 mm	28.0
653487	189	7 1/2	Drop Centre	Domed	16 x 16 mm / 10 x 13 mm	40.0

Shroud

Outside Diameter	Part Number
135 mm	604624
138 mm	604625
141 mm	604626
144 mm	604627
187 mm	601425

www.halcorocktools.com

United Kingdom

Halco Rock Tools Ltd
Armytage Road
Brighouse
West Yorkshire
HD6 1QF

Tel: +44 (0)1422 399900

Email: salesuk@halcorocktools.com

USA

Halco America LLC
2720 Fallon Drive
Sherman
TX 75090

Tel: +1 903-893-2300

Email: salesusa@halcorocktools.com

Australia

Halco Australia
Dillington Pass
Landsdale WA 6065

Tel: +61 8 9303 9506

Email: salesaus@halcorocktools.com

South Africa

Halco South Africa
21 Harriet Ave
Driehoek
Germiston 1459
Shop No4
Johannesburg

Email: salesafrica@halcorocktools.com



Halco Rock Tools
Quality Management System
is Certified to ISO9001: 2008
Certificate No: LRQ 0850659




anzeve
Queremos ayudarte

c/ Diego Marín Aguilera, 4
Parque Tecnológico de Leganés
28919 Leganés (Madrid). España
Tel.: +34 916 334 553
info@anzeve.com
www.anzeve.com